



P/N 410N11

AIR CONDITIONING FILLING BENCH

Categories: Hydraulic benches, air cooling & accessories, Services and maintenance benches

PRODUCT DESCRIPTION

It shall ensure to perform servicing (filling, draining) and maintenance (leak test, vacuum the system for trouble shooting) of the system during maintenance operations.

Including :

- 1 bench with 2 flexible pipes (4.5m)
- 1 suitcase with spare parts

+33 467 455 564

150, Rue Maurice Béjart

34080 Montpellier, FRANCE

contact@kit-aero.com

www.kit-aero.com

REFERENCED PARTNER

AIRBUS

- 1 suitcase with tools for oil injection
- 1 suitcase for pressure test
- 1 suitcase for gas a

 **TECHNICAL INFORMATION****APPLICABILITY**

AS332, AS355, AS365, AS366, AS532, AS555, AS565, Dauphin, Ecureuil, H120, H130, H155, H160, H175, H225, H225M, SA330, Super Puma

- Power supply : 220V 50/60 HZ
- Power consumption : 1000W
- Recovery capacity : 600 g/min
- Capacity recycling filters : 300 kg
- Emptying : pallet vaccum pump / flow rate of the vacuum pump : 180 L/min

Caractéristiques principales

- Storage temperature : -20°C to +70°C
- Operating temperature : +5°C to +50°C
- Load hoses length : 6 m Frigorigene fluid reservoir :
- Weighing the entire refrigerant chain
- Charge accuracy : +/- 10 g
- Capacity of the reserve in exploitable refrigerant : 35 kg
- Rinse in liquid phase Automatic features :
- Separation of used oil
- Injection of virgin oil
- Tracer injection

ATA 21-50

WEIGHT 180 kg

SIZE 81 x 55 x 120 cm