



P/N 410N11

AIR CONDITIONING FILLING BENCH

Catégories : Services and maintenance benches, Hydraulic benches, air cooling & accessories

PRODUCT DESCRIPTION

It shall ensure to perform servicing (filling, draining) and maintenance (leak test, vacuum the system for trouble shooting) of the system during maintenance operations.

Including :

- 1 bench with 2 flexible pipes (4.5m)
- 1 suitcase with spare parts

+33 467 455 564

150, Rue Maurice Béjart

34080 Montpellier, FRANCE

contact@kit-aero.com

www.kit-aero.com

REFERENCED PARTNER

AIRBUS

- 1 suitcase with tools for oil injection
- 1 suitcase for pressure test
- 1 suitcase for gas a

 **TECHNICAL INFORMATION****Applicabilité**

Dauphin, Ecureuil, H225M, Super Puma, AS332, AS355, AS365, AS366, AS532, AS555, AS565, H120, H130, H155, H160, H175, H225, SA330

- Power supply : 220V 50/60 HZ
- Power consumption : 1000W
- Recovery capacity : 600 g/min
- Capacity recycling filters : 300 kg
- Emptying : pallet vaccum pump / flow rate of the vacuum pump : 180 L/min

Caractéristiques principales

- Storage temperature : -20°C to +70°C
- Operating temperature : +5°C to +50°C
- Load hoses length : 6 m Frigorigene fluid reservoir :
- Weighing the entire refrigerant chain
- Charge accuracy : +/- 10 g
- Capacity of the reserve in exploitable refrigerant : 35 kg
- Rinse in liquid phase Automatic features :
- Separation of used oil
- Injection of virgin oil
- Tracer injection

ATA	21-50
WEIGHT	180 kg
SIZE	81 x 55 x 120 cm