KIT AERO



P/N KA2014

PORTABLE STARTER POWER SUPPLY 20AH (PSPS)

Catégories : Ground Power Unit & Starters, battery chargers, Services and maintenance benches

PRODUCT DESCRIPTION

A breakthrough for Ground Power Unit users, the PSPS can start aircraft engines whenever and wherever. It also comes in handy during maintenance tasks to provide abundant auxiliary power for avionics, on-board medical equipment, or any other accessory. Its self-monitoring features give you access to pertinent information such as battery health and state-of-charge through a LCD display.

The PSPS KIT (NSN: 2995-14-586-6147) includes **4 components** having the NATO Stock Number:

Component / Reference / NNO Code

- 1 Power unit (1) / KA2014-1 (*) / 2995-14-586-6183
- 1 Charger / KA2014-2 (**) / 6130-14-586-6187
- 1 Extension cable / KA2014-3 / 6150-14-586-6149
- 1 Box / KA2014-4 / 4920-14-586-6159

(*) Interchangeable references: KA2016-1-1 or KA2016-1-2
(**) Interchangeable reference: KA2016-2

+33 467 455 564
150, Rue Maurice Béjart
34080 Montpellier, FRANCE
contact@kit-aero.com
www.kit-aero.com

REFERENCED PARTNER AIRBUS

KIT AERO

TECHNICAL INFORMATION

Applicabilité	AS350, AS355, AS365, AS366, AS550, AS555, AS565, H120, H125, H130, H155, SA330, SA360
Caractéristiques principales	– Operating voltage: 16V-28V – Continuous current: 200A – Capacity : 20Ah Ipp/Ipr (14V and 25°C): 1,250A/950A – Operating Temperature: -20°C to 60°C (-4°F to 140°F) – Storage Temperature: -40°C to 60°C (-40°F to 140°F) – Quick recharge in-flight or in hangar: 60 min LCD display informs on : – Number of cycles – State of charge – Cell temperature – Voltage limits
ATA	24-00
SIZE	58 x 35 x 23,5 (cm) 1.90 x 1.15 x 0.77 (ft)
WEIGHT	17 (kg) 37.5 (lbs)
CERTIFICATION	CE, UN/DOT 38.3, MIL-STD-704F

+33 467 455 564
150, Rue Maurice Béjart
34080 Montpellier, FRANCE
contact@kit-aero.com
www.kit-aero.com

REFERENCED PARTNER
AIRBUS