
KIT AERO



P/N GB900-080-000

LANDING GEAR JACK

Catégories : Portable cranes, slings, jacks and accessories, Jacks

PRODUCT DESCRIPTION

Hydraulic Jack Wheel Change Mod. 5/3/102 is designed only to lift the H160 helicopter at its landing gear. The jack is used to perform wheel changes, it can also be used in the maintenance task servicing trains. The material consists of :

- 1 jack
- 2 spacers
- 1 pump
- 1 hose

Spacers allow to vary the heights of approaches.

TECHNICAL INFORMATION

Applicabilité	H160

+33 467 455 564
150, Rue Maurice Béjart
34080 Montpellier, FRANCE
contact@kit-aero.com
www.kit-aero.com

REFERENCED PARTNER AIRBUS

Caractéristiques principales	– Jack specifications closed height : 102 mm – Maximum load : 5000 kg – Hydraulic lift : 252 mm – Extended height 303 mm – Ball radius at adapter : 12,7 mm (1/2??) – Screw extension 51 mm – Length of base 350 mm – Operating temperature : -5?C to +50?C – Hydraulic fluid MIL-PRF-83282 – Oil system capacity 3 lt (total) Accessories : – Spacer type 1 H + 25 mm – Space type 2 H + 50 mm
ATA	07-10
WEIGHT	32 kg
SIZE	78,8 x 49,3 x 28,4 cm

+33 467 455 564
150, Rue Maurice Béjart
34080 Montpellier, FRANCE
contact@kit-aero.com
www.kit-aero.com

REFERENCED PARTNER
AIRBUS